

MODELS N-Series

N-Series Fiberglass

SPECIFICATIONS

Treatment Capacity ______ 500 to 1,500 G.P.D.

BOD Loading _____ 1.25 to 3.75 lbs.

Aerator _____ 2.4 to 7.2 scfm

Control Panel _____ Raintight

Electrical _____ 115V/60Hz



20" OPENING COVER -3" S/40 PVC AIR LINE -CONNECTION GRADE OUTLET INLET HIGH LEVEL -ALARM FLOAT CLARIFIER SURGE-CONTROL WEIR В AERATION AIRLINE -CHAMBER DIFFUSER -00-0

DIMENSIONS

| MODEL | Α | В | С |
|--------|-----|-----|-----|
| 500 N | 63" | 63" | 17" |
| 600 N | 76" | 55" | 17" |
| 750 N | 76" | 65" | 17" |
| 800 N | 76" | 67" | 17" |
| 1000 N | 76" | 87" | 17" |
| 1500 N | 96" | 82" | 24" |

U.S. Patent Numbers 5,221,470 · 5,770,081 · 5,785,854

US 8,038,874 B2 · US 6,358,411 B1 US 7,513,994 B2 · US 7,178,677 B1

Other Patents Pending



MODELS N-Series

| SPECIFICATIONS | | | | | | |
|----------------|--------------------|----------------|----------|---------------|--|--|
| MODEL | TREATMENT CAPACITY | BOD LOADING | AERATOR | CONTROL PANEL | | |
| 500N | 500 GPD | 1.25 lbs. | 2.4 scfm | Raintight | | |
| 600N | 600 GPD | 1.5 lbs. | 2.4 scfm | Raintight | | |
| 750N | 750 GPD | 1.85 lbs. | 3.6 scfm | Raintight | | |
| 800N | 800 GPD | 1.96 lbs. | 3.6 scfm | Raintight | | |
| 1000N | 1000 GPD | 2.5 lbs. | 4.8 scfm | Raintight | | |
| 1500N | 1500 GPD | 3.75 lbs. | 7.2 scfm | Raintight | | |
| 500NS | 500 GPD | 1.25 lbs. | 2.4 scfm | Raintight | | |

Other systems available from 500 to 1,500 GPD and NSF/ANSI Standard 40, 245, 350



Clearstream Systems are one of the finest aerobic wastewater systems available in the industry today. The high degree of treatment is accomplished at a remarkably low operating cost per month. 500N Clearstream Wastewater Systems are in full compliance with NSF/ANSI Standard 40.



Clearstream Systems provides a two-year warranty on its equipment, without hidden conditions. We are confident of the durability and quality of our systems, so our warranty is simple. If the equipment is defective, we will either replace it with new components or repair the existing component at no charge.



Aerators, control panels, and accessory equipment from Clearstream Systems are manufactured according to the strictest guidelines. We have a long history of providing our customers with the most reliable components created with top quality materials while still being offered at a reasonable price.

Corporate Office (409) 755-1500 · Toll Free (800) 586-3656 · Fax (409) 755-6500 4899 U.S. Hwy 69S · Lumberton, Texas 77657 · www.clearstreamsystems.com